

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

STN Karlsruhe

L2 ANSWER 1 OF 1 WPIDS COPYRIGHT 2004 THOMSON DERWENT on STN

ACCESSION NUMBER: 2000-001612 [01] WPIDS
 DOC. NO. NON-CPI: N2000-001376
 DOC. NO. CPI: C2000-000477
 TITLE: Method of making a pipe lagged with a spiral-wound external protective envelope.
 DERWENT CLASS: A88 H03 Q67
 INVENTOR(S): MARCHAL, P; RIVIER, M
 PATENT ASSIGNEE(S): (ITPI-N) ITP; (ITPI-N) ITP SA
 COUNTRY COUNT: 25
 PATENT INFORMATION:

PATENT NO	KIND	DATE	WEEK	LA	PG	MAIN	IPC
FR 2777628	A1	19991022	(200001)*		20	F16L059-14	
EP 1070907	A1	20010124	(200107)#	FR		F16L059-02	<---

R: AL AT BE CH CY DE DK ES FI FR GB GR IE IT LI LT LU LV MC MK NL PT
 RO SE SI


APPLICATION DETAILS:

PATENT NO	KIND	APPLICATION	DATE
FR 2777628	A1	FR 1998-4819	19980417
EP 1070907	A1	EP 1999-401824	19990720

PRIORITY APPLN. INFO: FR 1998-4819 19980417; EP 1999-401824
 19990720

INT. PATENT CLASSIF.:
 MAIN: F16L059-02; F16L059-14
 SECONDARY: F16L011-08

GRAPHIC INFORMATION:



BASIC ABSTRACT:

FR 2777628 A UPAB: 20000105
 NOVELTY - The pipe (1) has an external envelope (4) with an intermediate annular layer (3) of insulating material surrounding an internal tube (2) of the pipe. The method includes winding a non-elastic wire (40) around

STN Karlsruhe

the insulating material in a spiral so the spirals join to form the envelope with its mechanical properties protecting the intermediate layer.

DETAILED DESCRIPTION - The insulating material of the intermediate layer is a high porosity micro porous material with open pores forming a coherent 3-dimensional structure, giving sufficient flexibility to be wound around the internal tube. The round section wire is steel with a density greater than six. The wire is wound under conditions so that the wire is non-elastic and the moment force applied is insufficient to damage the insulating layer. Winding the wire around the internal tube and insulating layer is done by rotating the tube about a first horizontal axis. The wire is supplied on a bobbin turning freely about a second horizontal axis and guides between the bobbin and the rotating tube exert a force at the tube which passes the elastic limit of the wire and pulls sufficiently little on the insulating material that it is not crushed or damaged. The moment is obtained by lengthening the vertical guide to provide a lifting arm to obtain the desired moment. The internal tube is covered by at least one layer of insulating material and the armor by a sealing layer (5) of elasto-plastic material, preferably polyolefin-based such as a polyethylene resin. The wire is partly embedded in the insulating material. The external sealing layer covers the outside of the wire spirals. The insulating material is a mixture of silica powder and ceramic reinforcement fibers, compacted in a coherent 3-dimensional structure with high porosity and open pores contained in an envelope which is not gas-tight, in the form of self-supporting bands which can be rolled onto the internal tube. The external layer also covers the connections between successive pipes, where the ends of the wires can be advantageously welded together.

USE - In particular for constructing submarine pipelines to carry petroleum products.

ADVANTAGE - Ensuring good quality insulation.

DESCRIPTION OF DRAWING(S) - Schematic section of lagged pipe.

Internal tube 2

Insulating layer 3

External armor envelope 4

Sealing layer 5

Wire 40

Dwg.1/2

FILE SEGMENT: CPI GMPI

FIELD AVAILABILITY: AB; GI

MANUAL CODES: CPI: A12-H02D1; A12-S04B; H03-B